

断面詳細 S=1/3

The drawing consists of two parts. The left part is a longitudinal section of a bridge deck, showing a total width of 2280 mm. The width is divided into segments of 150, 450, 450, 450, 450, and 150 mm. The right part is a detailed cross-section of the deck slab, showing the internal structure and reinforcement. It includes dimensions of 180, 2100, 2095, and 2060 mm. The cross-section is labeled with numbers 1 through 14, indicating specific components and reinforcement details.

Technical drawing of a double-door opening (Figure 10-10). The drawing shows a side elevation of a wall with two doors. The overall width is 2460, and the overall height is 2600. The opening height is 2050. The door height is 2140. The door width is 1025. The door is labeled with callouts 13, 16, 17, and 18. The door is shown in a closed position. The drawing includes dimensions for the door frame, the opening, and the overall structure. The door is labeled with callouts 13, 16, 17, and 18. The door is shown in a closed position. The drawing includes dimensions for the door frame, the opening, and the overall structure.

表示呼名	表示呼寸	表示有効寸法
1221	H1200×W2100	H1174×W2060

Technical drawing showing a cross-section of a two-part assembly. The drawing includes dimensions and callouts for various components.

Dimensions:

- Overall height: 1200
- Overall width: 200
- Top section height: 196
- Top section width: 3.5
- Top section depth: 16.5
- Bottom section height: 1198
- Bottom section width: 1.5
- Bottom section depth: 18.5
- Internal height: 1174.5
- Internal width: 11
- Internal depth: 1
- Bottom flange thickness: 20
- Top flange thickness: 20

Callouts:

- 7: Points to the top flange.
- 8: Points to the bottom flange.
- 9: Points to the internal structure.
- 15: Points to the internal structure.

品 種	SOWサイン
品 番	SOW-NAH1221
図面番号	KRSH22072